



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** LPS® Dry Film Silicone Lubricant  
**Other means of identification**  
**Part Number** 01616, C01616  
**Recommended use** A dry film industrial lubricant for rubber, plastic and metal parts.  
**Recommended restrictions** None known.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** ITW Pro Brands  
**Address** 4647 Hugh Howell Rd.  
Tucker, GA 30084  
**Country** (U.S.A.)  
Tel: +1 770-243-8800  
**In Case of Emergency** 1-800-424-9300  
1-703-527-3887  
**Website** www.lpslabs.com  
**E-mail** lpssds@itwprobrands.com

#### Supplier

ITW Permatex Canada  
1-35 Brownridge Road  
Halton Hills, ON, L7G 0C6  
Canada  
1-800-241-8334

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
Gases under pressure Liquefied gas  
**Health hazards** Skin corrosion/irritation Category 2  
Reproductive toxicity Category 2  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Specific target organ toxicity, repeated exposure (inhalation) Category 2 (nervous system)  
**Environmental hazards** Not classified.

### Label elements



#### Signal word

Danger

#### Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.

#### Precautionary statement

##### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

<b>Response</b>	If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
<b>Storage</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Other hazards</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,1-Difluoroethane (HFC-152a)		75-37-6	50 - 60
2-METHYLPENTANE		107-83-5	10 - 20
2,3-DIMETHYLBUTANE		79-29-8	5 - 10
3-Methylpentane		96-14-0	5 - 10
ISOPROPANOL		67-63-0	1 - 5
NEOHEXANE		75-83-2	1 - 5
Poly (Dimethylsiloxane)		63148-62-9	1 - 5
N-HEXANE		110-54-3	1 - 2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

## Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

## General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

### Environmental precautions

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values Components

Components	Type	Value
2,3-DIMETHYLBUTANE (CAS 79-29-8)	STEL	1000 ppm
2-METHYLPENTANE (CAS 107-83-5)	TWA	500 ppm
	STEL	1000 ppm
3-Methylpentane (CAS 96-14-0)	TWA	500 ppm
	STEL	1000 ppm
ISOPROPANOL (CAS 67-63-0)	TWA	500 ppm
	STEL	400 ppm
NEOHEXANE (CAS 75-83-2)	TWA	200 ppm
	STEL	1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
	TWA	500 ppm
N-HEXANE (CAS 110-54-3)	TWA	50 ppm

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
2-METHYLPENTANE (CAS 107-83-5)	STEL	3500 mg/m3
	TWA	1000 ppm
	TWA	1760 mg/m3
3-Methylpentane (CAS 96-14-0)	STEL	500 ppm
	STEL	3500 mg/m3
	TWA	1000 ppm
	TWA	1760 mg/m3
ISOPROPANOL (CAS 67-63-0)	STEL	500 ppm
	STEL	984 mg/m3
	TWA	400 ppm
	TWA	492 mg/m3
N-HEXANE (CAS 110-54-3)	TWA	200 ppm
	TWA	176 mg/m3
	TWA	50 ppm

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-HEXANE (CAS 110-54-3)	TWA	20 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value
2,3-DIMETHYLBUTANE (CAS 79-29-8)	STEL	1000 ppm
	TWA	500 ppm
2-METHYLPENTANE (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm
	TWA	500 ppm
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
NEOHEXANE (CAS 75-83-2)	STEL	1000 ppm
	TWA	500 ppm
N-HEXANE (CAS 110-54-3)	TWA	50 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-HEXANE (CAS 110-54-3)	TWA	50 ppm

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value
ISOPROPANOL (CAS 67-63-0)	STEL	1230 mg/m <sup>3</sup>
	TWA	500 ppm
		983 mg/m <sup>3</sup>
N-HEXANE (CAS 110-54-3)	TWA	400 ppm
		176 mg/m <sup>3</sup>
		50 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ISOPROPANOL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
N-HEXANE (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****Canada - Alberta OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Canada - Quebec OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

**Physical state** Gas.

**Form** Aerosol.

**Color** Colorless.

**Odor** Isohexane.

<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	< 1.4 °F (< -17.0 °C) Tag Closed Cup
<b>Evaporation rate</b>	< 1 (Ethyl Ether = 1)
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	55 psig @ 25°C
<b>Vapor density</b>	~ 3 (air = 1)
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	< 10 % w/w
<b>Partition coefficient (n-octanol/water)</b>	> 1
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	< 14 cSt @ 25°C
<b>Other information</b>	
<b>Density</b>	6.23
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>Specific gravity</b>	0.75
<b>VOC</b>	41 % per US State & Federal Consumer Product Regulations

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain.

### Information on toxicological effects

Components	Species	Test Results
1,1-Difluoroethane (HFC-152a) (CAS 75-37-6)		
<b>Acute</b>		
<b>Inhalation</b>		
<i>Gas</i>		
LC50	Rat	> 437500 ppm, 4 Hours
ISOPROPANOL (CAS 67-63-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	16.4 ml/kg, 24 Hours
<b>Oral</b>		
LD50	Rat	4.7 g/kg
N-HEXANE (CAS 110-54-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 5 ml/kg, 4 Hours
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	73860 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	49 ml/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
<b>ACGIH Carcinogens</b>		
ISOPROPANOL (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
<b>Canada - Manitoba OELs: carcinogenicity</b>		
ISOPROPANOL (CAS 67-63-0)	Not classifiable as a human carcinogen.	
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.	
<b>Aspiration hazard</b>	Not an aspiration hazard.	
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.	
<b>Further information</b>	None known.	

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
ISOPROPANOL (CAS 67-63-0)		
<b>Aquatic</b>		
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )
		> 1400 mg/l, 96 hours

Components	Species	Test Results
N-HEXANE (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 2.101 - 2.981 mg/l, 96 hours
Poly (Dimethylsiloxane) (CAS 63148-62-9)		
<b>Aquatic</b>		
Fish	LC50	Channel catfish ( <i>Ictalurus punctatus</i> ) 2.36 - 4.15 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

LPS® Dry Film Silicone Lubricant	> 1
1,1-Difluoroethane (HFC-152a)	0.75
2,3-DIMETHYLBUTANE	3.42
2-METHYLPENTANE	3.74
3-Methylpentane	3.6
ISOPROPANOL	0.05
NEOHEXANE	3.82
N-HEXANE	3.9

**Mobility in soil** No data available.

**Other adverse effects** None known.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

D001: Waste Flammable material with a flash point <140 F

D003: Waste Reactive material

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### 14. Transport information

**TDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.



**Other information**

**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-D, S-U  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**IATA; IMDG; TDG**



**General information** Ensure compliance with applicable regulations.

**15. Regulatory information****Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

1,1-Difluoroethane (HFC-152a) (CAS 75-37-6)

**Precursor Control Regulations**

Not regulated.

**International regulations****Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.

**Kyoto protocol**

Not applicable.

**Montreal Protocol**

Not applicable.

**Basel Convention**

Not applicable.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

**Issue date** 06-20-2016

**Version #** 01

**Disclaimer** ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.