



SAFETY DATA SHEET

1. Identification

Product identifier LPS® Micro-X
Other means of identification
Part Number 04516, C04516
Recommended use A fast drying industrial cleaning solvent designed to remove soil and other contaminants.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands
Address 4647 Hugh Howell Rd.
Tucker, GA 30084
Country (U.S.A.)
Tel: +1 770-243-8800
In Case of Emergency 1-800-424-9300
1-703-527-3887
Website www.lpslabs.com
E-mail lpssds@itwprobrands.com

Supplier

ITW Permatex Canada
1-35 Brownridge Road
Halton Hills, ON, L7G 0C6
Canada
1-800-241-8334

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Gases under pressure Compressed gas
Health hazards Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Reproductive toxicity Category 2
Specific target organ toxicity, single exposure Category 3 narcotic effects
Environmental hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.
Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	IF exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water/soap. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-METHYLPENTANE		107-83-5	70 - 80
ISOPROPANOL		67-63-0	5 - 15
PENTANE		109-66-0	1 - 10
CARBON DIOXIDE		124-38-9	1 - 5
N-HEXANE		110-54-3	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or Poison Control Center immediately.
Ingestion	Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Narcosis. Behavioral changes. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Fire may produce irritating, corrosive and/or toxic gases. By heating and fire, harmful vapors/gases may be formed. Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use standard firefighting procedures and consider the hazards of other involved materials. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. In the event of fire, cool tanks with water spray. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue. Water runoff can cause environmental damage.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Consider initial downwind evacuation for at least 500 meters (1/3 mile). Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Extinguish all flames in the vicinity. Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use foam to blanket spilled material. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Should be handled in closed systems, if possible. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Use non-sparking tools and explosion-proof equipment.

Avoid contact during pregnancy/while nursing. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure.

Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Keep away from heat, sparks and open flame. Eliminate sources of ignition.

Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
2-METHYLPENTANE (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
CARBON DIOXIDE (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-HEXANE (CAS 110-54-3)	TWA	50 ppm
PENTANE (CAS 109-66-0)	TWA	1000 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
2-METHYLPENTANE (CAS 107-83-5)	STEL	3500 mg/m3
	TWA	1000 ppm 1760 mg/m3
CARBON DIOXIDE (CAS 124-38-9)	STEL	500 ppm 54000 mg/m3
	TWA	30000 ppm 9000 mg/m3
ISOPROPANOL (CAS 67-63-0)	STEL	5000 ppm 984 mg/m3
	TWA	400 ppm 492 mg/m3
N-HEXANE (CAS 110-54-3)	TWA	200 ppm 176 mg/m3 50 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
CARBON DIOXIDE (CAS 124-38-9)	STEL	15000 ppm
	TWA	5000 ppm
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-HEXANE (CAS 110-54-3)	TWA	20 ppm
PENTANE (CAS 109-66-0)	TWA	600 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
2-METHYLPENTANE (CAS 107-83-5)	STEL	1000 ppm
	TWA	500 ppm
CARBON DIOXIDE (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-HEXANE (CAS 110-54-3)	TWA	50 ppm
PENTANE (CAS 109-66-0)	TWA	1000 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
CARBON DIOXIDE (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-HEXANE (CAS 110-54-3)	TWA	50 ppm
PENTANE (CAS 109-66-0)	TWA	600 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
CARBON DIOXIDE (CAS 124-38-9)	STEL	54000 mg/m3
	TWA	30000 ppm 9000 mg/m3
ISOPROPANOL (CAS 67-63-0)	STEL	5000 ppm 1230 mg/m3
	TWA	500 ppm 983 mg/m3
N-HEXANE (CAS 110-54-3)	TWA	400 ppm 176 mg/m3
PENTANE (CAS 109-66-0)	TWA	50 ppm 350 mg/m3 120 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ISOPROPANOL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
N-HEXANE (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**Canada - Alberta OELs: Skin designation**

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

N-HEXANE (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection	
Hand protection	For prolonged or repeated skin contact use suitable protective gloves. Chemical resistant gloves are recommended.
Other	Avoid contact with the skin. Wear appropriate chemical resistant clothing.
Respiratory protection	No personal respiratory protective equipment normally required. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	None known.
General hygiene considerations	When using do not smoke. When using, do not eat, drink or smoke. Wash hands after handling. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid.
Physical state	Gas.
Form	Aerosol.
Color	Clear water-white
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	140.9 °F (60.5 °C) dispensed liquid
Flash point	< 1.4 °F (< -17.0 °C) Tag Closed Cup
Evaporation rate	< 1 (Ethyl Ether = 1)
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 %
Flammability limit - upper (%)	7 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	352.53 mm Hg @ 38°C
Vapor density	~3 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 10 % w/w
Partition coefficient (n-octanol/water)	> 1
Auto-ignition temperature	582.8 °F (306 °C)
Decomposition temperature	Not available.
Viscosity	< 3 cSt @ 25°C
Other information	
Heat of combustion	> 30 kJ/g
Percent volatile	100 %
Specific gravity	0.64 - 0.67 @ 20°C
VOC	96.2 % per U.S, State and Federal Consumer Product Regulations; 669 g/L per SCAQMD Rule 102

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition. Instability caused by elevated temperatures.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Aerosol containers are unstable at temperatures above 50°C. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents. Isocyanates. Acids. Chlorine. Do not mix with other chemicals.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Skin contact	Causes skin irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Defatting of the skin. Irritating to eyes and respiratory system. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test Results
ISOPROPANOL (CAS 67-63-0)		
Acute		
Oral		
LD50	Rat	4.7 g/kg
N-HEXANE (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
PENTANE (CAS 109-66-0)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

ACGIH Carcinogens

ISOPROPANOL (CAS 67-63-0) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ISOPROPANOL (CAS 67-63-0) Not classifiable as a human carcinogen.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure Narcotic effects.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects None known.

Further information None known.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
ISOPROPANOL (CAS 67-63-0)		
Aquatic		
Fish	LC50 Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/l, 96 hours
N-HEXANE (CAS 110-54-3)		
Aquatic		
Fish	LC50 Fathead minnow (<i>Pimephales promelas</i>)	2.101 - 2.981 mg/l, 96 hours

Persistence and degradability Not inherently biodegradable.

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

LPS® Micro-X	> 1
2-METHYLPENTANE	3.74
ISOPROPANOL	0.05
N-HEXANE	3.9
PENTANE	3.39

Mobility in soil Readily absorbed into soil.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code Not regulated.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable, MARINE POLLUTANT
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	Yes
Special precautions for user	Not available.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No.
ERG Code	2X
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950
UN proper shipping name AEROSOLS, flammable, MARINE POLLUTANT
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not available.
Environmental hazards
Marine pollutant Yes
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

IATA; IMDG; TDG**Marine pollutant**

General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

CARBON DIOXIDE (CAS 124-38-9)

Precursor Control Regulations

Not regulated.

International regulations The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

CARBON DIOXIDE (CAS 124-38-9) Listed.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	05-18-2016
Revision date	03-23-2017
Version #	03
Further information	HMIS® is a registered trade and service mark of the NPCA.

References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
Korea. Accidental Release Prevention Substances (Presidential Decree of Toxic Chemical Control Law, Executive Order No. 19203)
Korea. Dangerous Substances Threshold Quantity (Presidential Decree of Dangerous Substances Safety Management Act No. 18406, Schedule 1)
Korea. Harmful Substances Prohibited from Manufacturing (Presidential Decree on the Industrial Safety and Health Act (No. 13053), Article 29)
Korea. Harmful Substances Requiring Permission for Manufacture or Use (Presidential Decree on the Industrial Safety and Health Act (No. 13053), Article 30)
Korea. Non-Toxic Chemicals List (National Institute of Environment Research (NIER) Public Notice No. 1997-10, as amended)
Korea. Observational Chemicals (Ministerial Decree of TCCL Article 6)
Korea. OELs. Regulation for Permitted Concentration of Hazardous Substances (Ministry of Labor (MOL) Public Notice No. 1986-45, as amended)
Korea. Prohibited Chemical Substances (TCCL Article 11)
Korea. Regulated volatile organic compounds (VOCs) (MOE Notice No. 2001-36, March 8, 2001, as amended)
Korea. Restricted Chemical Substances (TCCL Article 11)
Korea. Toxic Chemical Control Law (TCCL), Existing Chemicals Inventory (KECI)
Korea. Toxic Chemical Control Law (TCCL), pre-1997 List
Korea. Toxic Chemicals (TCCL Article 10)
Korea. Toxic Release Inventory (TRI) Chemicals (TCCL Article 14)
Taiwan. Dangerous Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials)
Taiwan. Industrial Precursor Chemicals (Categories and Regulations Governing Inspection and Declaration of Industrial Precursor Chemicals, MOEA Decree No. 87, as amended)
Taiwan. OELs. (Standards on Workplace Atmosphere of Dangerous and Hazardous Materials)
Taiwan. Toxic Chemical Substances (TCS) (List of Toxic Chemical Substances announced by the Environmental Protection Administration)
Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials)
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits
GOST 30333-2007 - Chemical production safety passport. General requirements
JIS Z 7252:2009 Classification of chemicals based on "Globally Harmonized System of Classification and Labelling of Chemicals (GHS)"
JIS Z 7253:2012 Hazard communication of chemicals based on GHS – Labelling and Safety Data Sheet (SDS)
Japan Chemical Industry Association (JCIA) GHS Guideline, June 2012

Disclaimer

This safety data sheet was prepared in accordance with JIS Z 7253:2012. Additional information is given in the Material Safety Data Sheet. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Hazard(s) identification: Hazard statement
Hazard(s) identification: Prevention
Hazard(s) identification: Response
Hazard(s) identification: GHS Symbols
Handling and storage: Precautions for safe handling
Toxicological information: Reproductivity
Regulatory Information: Risk Phrases - Labeling
GHS: Classification